Compact525

5 Litre Oxygen Concentrator





Compact525



S P E C I F I C A T I O N S

Dimension (H x W x D) 62.2 x 34.2 x 30.4 cm

Weight 16.3 kg

Flowrate 0.5 to 5 l / min

Oxygen Concentration at 0.5 - 5 l / min 93% ± 3%

Electrical Requirements 230 V, 50/60 Hz

Power Consumption approx. 290 Watt at 2 l/min. approx. 312 Watt at 5 l/min.

Classification II Type B

Manufacturing products that are of the highest possible quality is key to **DeVilbiss Healthcare. The latest** Compact 525 oxygen concentrator is designed and built to meet the high demands of patients and cost challenges faced by service providers.

In commitment to our quality aims, we have invested in new manufacturing processes and innovative production techniques. The new black, Compact 525 is now manufactured at our dedicated oxygen therapy facility in Pennsylvania, USA, which has given us the control to deliver a reliable, high quality, more eco-friendly oxygen concentrator.

Delivering up to 5 litres per minute with high oxygen concentration across all



Compact 525



Front label with easy to read pictograms



Humidifier



Paediatric Flowmeter

Distributor:

DeVilbiss

DeVilbiss Healthcare Ltd. Unit 3, Bloomfield Park, Bloomfield Road Tipton, West Midlands DY4 9AP United Kingdom Phone + 44 (0) 121 521 3140 + 44 (0) 121 521 3141 www.devilbisshc.com enquiries@devilbisshc.com

DeVilbiss Healthcare has a policy of continuing improvement, we therefore reserve the right to vary details at any time without notice. OSD is a registered trademark of DeVilbiss Healthcare.

flow rates and adopting the latest developments in the reduction of sound and power consumption, the latest Compact 525 increases patient comfort and lowers operating costs.

Added features

- Improved sound level reduction our quietest concentrator yet
- Front label with easy to read pictograms
- New black colour

Service and maintenance friendly

- 2 part case design
- 3 years warranty as standard (an optional extended 2 year warranty package available)

Patient safety features

- OSD[®] Sensor for continuously monitoring oxygen levels
- Visual and audible alarms for low oxygen levels, power failure, pressure drop and service required
- Oxygen outlet incorporating a fire protection adapter

Environmentally friendly

- Intelligent power management system utilises Turn-Down Technology providing less power consumption below flow rates of 2.5 l/min
- Reduced packaging: reducing materials and waste, as well as transportation costs and emissions without compromising product protection

